

C 568 EB

SHOTGUN MICROPHONE



Combined pressure gradient/interference microphone. Hypercardioid below about 500 Hz, continuously increasing directivity above 500 Hz. Switchable bass cut. Matte black all-metal case.

Shotgun microphones efficiently reject sounds from the sides. The C 568 EB is the microphone of choice for film, TV, video, lectern, or stage front distant miking.

STANDARD ACCESSORIES

SA 40 Stand adapter
W 68 Foam windscreen

OPTIONAL ACCESSORIES

H 30 Shock-mount/stand adapter
H 38 Small shock-mount
SA 38/H Small shock-mount/stand adapter
B 18 Battery power supply
N 62, N 66 AC power supplies

SPECIFICATIONS

Polar Pattern:	hypercardioid/directional
Frequency Range:	20 – 20,000 Hz
Sensitivity:	11 mV/Pa
Impedance:	600 ohms
Equivalent Noise Level:	28 dB (CCIR 468-2) 18 dB·A (DIN 45412-A)
S/N Ratio:	76 dB
Max. SPL for 0.5% THD:	128 dB
Size:	21 Ø x 255 mm (0.8 Ø x 10 in.)
Net/Shipping Weight:	175/650 g (6.2 oz./1.4 lbs.)

