





SOD-123



Mounting Pad Layout



Features

- Silicon Epitaxial Planar Diode Switches
- For electric bandswitching in radio and TV tuners in the frequency range of 50...1000 MHz. The dynamic forward resistance is constant and very small over a wide range of frequency and forward current. The reverse capacitance is also small and largely independent of the reverse voltage.
- These diodes are also available in SOD-323 case with the type designations BA782S and BA783S.

Mechanical Data

Case: SOD-123 plastic case

Weight: approximately 0.01g

Cathode Band Color: Blue

Packaging Codes/Options:

D3/10K per 13" reel (8mm tape), 30K/box

D4/3K per 7" reel (8mm tape), 30K/box

Maximum Ratings and Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	Value	Unit
Reverse Voltage	V_R	35	V
Forward Continuous Current at $T_{amb} = 25^\circ\text{C}$	I_F	100	mA
Junction Temperature	T_j	125	$^\circ\text{C}$
Storage Temperature Range	T_s	-55 to +125	$^\circ\text{C}$

Electrical Characteristics


Ratings at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage	V _F	I _F = 100mA	—	—	1	V
Leakage Current	I _R	V _R = 20V	—	—	50	nA
Dynamic Forward Resistance	r _f	f = 50...1000MHz, I _F = 3mA	—	—	0.7	Ω
		f = 50...1000MHz, I _F = 10mA	—	—	1.2	
Capacitance	C _{tot}	V _R = 1V, f = 1MHz	—	—	1.5	pF
		V _R = 3V, f = 1MHz	—	—	1.25	
Series Inductance across Case	L _S	—	—	2.5	—	nH

Ratings and Characteristic Curves

(T_A = 25°C unless otherwise noted)

Capacitance versus reverse voltage



Dynamic forward resistance versus forward voltage

