

FAST RECOVERY RECTIFIER DIODES


- LOW FORWARD VOLTAGE DROP
- HIGH SURGE CURRENT CAPABILITY

APPLICATIONS

- AC-DC POWER SUPPLIES AND CONVERTERS
- FREE WHEELING DIODES, etc.

DESCRIPTION

Their high efficiency and high reliability combined with small size and low cost make these fast recovery rectifier diodes very attractive components for many demanding applications.



ABSOLUTE RATINGS (limiting values)

| Symbol | Parameter | | Value | Unit |
|--------------------|--|----------------------------|-------------|------------|
| I_{FRM} | Repetitive Peak Forward Current | $t_p \leq 20\mu s$ | 100 | A |
| $I_{F(AV)}$ | Average Forward Current* | $T_a = 90^\circ C$ | 3 | A |
| I_{FSM} | Surge non Repetitive Forward Current | $t_p = 10ms$ Sinusoidal | 150 | A |
| P_{Tot} | Power Dissipation* | $T_a = 90^\circ C$ | 3.5 | W |
| T_{stg} T_j | Storage and Junction Temperature Range | | - 40 to 175 | $^\circ C$ |
| T_L | Maximum Lead Temperature for Soldering during 10s at 4mm from Case | | 230 | $^\circ C$ |

| Symbol | Parameter | PFR | | | | | Unit |
|-----------|-------------------------------------|-----|-----|-----|-----|-----|------|
| | | 850 | 851 | 852 | 854 | 856 | |
| V_{RRM} | Repetitive Peak Reverse Voltage | 50 | 100 | 200 | 400 | 600 | V |
| V_{RSM} | Non Repetitive Peak Reverse Voltage | 75 | 150 | 250 | 450 | 650 | V |

THERMAL RESISTANCE

| Symbol | Parameter | Value | Unit |
|---------------|-------------------|-------|--------------|
| $R_{th(j-a)}$ | Junction-ambient* | 25 | $^\circ C/W$ |

* On infinite heatsink with 10mm lead length.

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS

| Symbol | Test Conditions | | Min. | Typ. | Max. | Unit |
|--------|---------------------------|-------------------|------|------|------|---------------|
| I_R | $T_j = 25^\circ\text{C}$ | $V_R = V_{RRM}$ | | | 10 | μA |
| | $T_j = 100^\circ\text{C}$ | | | | 500 | |
| V_F | $T_j = 25^\circ\text{C}$ | $I_F = 3\text{A}$ | | | 1.25 | V |

RECOVERY CHARACTERISTICS

| Symbol | Test Conditions | | Min. | Typ. | Max. | Unit |
|----------|--|--|---------------|------|------|------|
| t_{rr} | $T_j = 25^\circ\text{C}$ $V_R = 30\text{V}$ | $I_F = 1\text{A}$ | PFR 850 → 854 | | | 150 |
| | | $d_{iF}/dt = -25\text{A}/\mu\text{s}$ | | | | |
| I_{RM} | $T_j = 25^\circ\text{C}$ $V_R = 30\text{V}$ | $I_F = 1\text{A}$ $d_{iF}/dt = -25\text{A}/\mu\text{s}$ | | | 2 | A |





Fig.1 Recovered charge versus d_{iF}/dt (typical values).






Fig.2 - Mean forward current I_D versus ambient temperature (maximum values).






Fig.3 - Thermal resistance versus lead length (maximum values).

Mounting n°1 : INFINITE HEATSINK



Mounting n°2 : PRINTED CIRCUIT



Mounting n°3 :
 $L = 10$ mm
 $R_{th} = 55$ °C/W





Fig.4 - Mean power dissipation versus mean forward current I for different rectifying types, in the case of :
 - a resistive load ($a = 1.57$)
 - a capacitive load ($a > 1.57$)




Fig.5 - Transient thermal impedance junction-ambient for mounting n°2 versus pulse duration ($L = 10$ mm)




Fig.6 - Non repetitive surge peak forward current versus number of cycles.





Fig.3a/3b - Peak forward current versus peak forward voltage drop.




Fig.8 - Non repetitive surge peak forward current for a sinusoidal pulse with width : $t \leq 10 \text{ ms}$, and corresponding value of I^2t .




Fig.9 - Capacity C versus reverse applied voltage V_R (typical values).