



# STPS745D/F/G

## POWER SCHOTTKY RECTIFIER

### MAIN PRODUCT CHARACTERISTICS

|             |        |
|-------------|--------|
| $I_{F(AV)}$ | 7.5 A  |
| $V_{RRM}$   | 45 V   |
| $V_F$       | 0.57 V |


### FEATURES AND BENEFITS

- VERY SMALL CONDUCTION LOSSES
- NEGLIGIBLE SWITCHING LOSSES
- EXTREMELY FAST SWITCHING
- LOW FORWARD VOLTAGE DROP
- INSULATED PACKAGE: ISOWATT220AC  
Insulating voltage = 2000V DC  
Capacitance = 12pF
- SMD PACKAGE

### DESCRIPTION

Single Schottky rectifier suited for Switch Mode Power Supply and high frequency DC to DC converters.

This device is intended for use in low voltage, high frequency inverters, free wheeling and polarity protection applications.



### ABSOLUTE RATINGS (limiting values)

| Symbol       | Parameter                                 |                              | Value  | Unit             |   |
|--------------|---|------------------------------|--|------------------|---|
| $V_{RRM}$    | Repetitive peak reverse voltage           |                              | 45   | V                |   |
| $I_{F(RMS)}$ | RMS forward current                       |                              | 20   | A                |   |
| $I_{F(AV)}$  | Average forward current<br>$\delta = 0.5$ | TO-220AC/ D <sup>2</sup> PAK | $T_c = 135^\circ\text{C}$                    | 7.5              | A |
|              |   | ISOWATT220AC                 | $T_c = 120^\circ\text{C}$                    |                  |   |
| $I_{FSM}$    | Surge non repetitive forward current      |                              | $t_p = 10 \text{ ms}$<br>Sinusoidal          | 150              | A |
| $I_{RRM}$    | Repetitive peak reverse current           |                              | $t_p = 2 \mu\text{s}$<br>$F = 1 \text{ kHz}$ | 1                | A |
| $T_{stg}$    | Storage Temperature Range                 |                              | - 65 to + 150                                | $^\circ\text{C}$ |   |
| $T_j$        | Maximum junction temperature              |                              | 150  | $^\circ\text{C}$ |   |
| dV/dt        | Critical rate of rise of reverse voltage  |                              | 10000  | V/ $\mu\text{s}$ |   |

## STPS745D/F/G

### THERMAL RESISTANCES

| Symbol        | Parameter        |                               | Value | Unit |
|---------------|------------------|-------------------------------|-------|------|
| $R_{th(j-c)}$ | Junction to case | TO-220AC / D <sup>2</sup> PAK | 3.0   | °C/W |
|               |                  | ISOWATT220AC                  | 5.5   |      |


### STATIC ELECTRICAL CHARACTERISTICS

| Symbol     | Parameter               | Tests Conditions          |                      | Min. | Typ. | Max. | Unit          |
|------------|-------------------------|---------------------------|----------------------|------|------|------|---------------|
| $I_R^*$    | Reverse leakage current | $T_j = 25^\circ\text{C}$  | $V_R = V_{RRM}$      |      |      | 100  | $\mu\text{A}$ |
|            |                         | $T_j = 125^\circ\text{C}$ |                      |      |      | 15   | $\text{mA}$   |
| $V_F^{**}$ | Forward voltage drop    | $T_j = 25^\circ\text{C}$  | $I_F = 15\text{ A}$  |      |      | 0.84 | V             |
|            |                         | $T_j = 125^\circ\text{C}$ | $I_F = 15\text{ A}$  |      |      | 0.72 |               |
|            |                         | $T_j = 125^\circ\text{C}$ | $I_F = 7.5\text{ A}$ |      |      | 0.57 |               |


Pulse test : \*  $t_p = 5\text{ ms}$ ,  $\delta < 2\%$   
 \*\*  $t_p = 380\text{ }\mu\text{s}$ ,  $\delta < 2\%$

To evaluate the conduction losses use the following equation :  
 $P = 0.42 \times I_{F(AV)} + 0.020 I_{F(RMS)}^2$


**Fig. 1:** Average forward power dissipation versus average forward current.




**Fig. 2-1:** Average current versus ambient temperature ( $\delta = 0.5$ ) (TO-220AC and D<sup>2</sup>PAK).




**Fig. 2-2:** Average current versus ambient temperature ( $\delta = 0.5$ ) (ISOWATT220AC).




**Fig. 3-1:** Non repetitive surge peak forward current versus overload duration (maximum values) (TO-220AC and D<sup>2</sup>PAK).




**Fig. 3-2:** Non repetitive surge peak forward current versus overload duration (maximum values) (ISOWATT220AC).




**Fig. 4-1:** Relative variation of thermal transient impedance junction to case versus pulse duration (TO-220AC and D<sup>2</sup>PAK).




**Fig. 4-2:** Relative variation of thermal transient impedance junction to case versus pulse duration (ISOWATT220AC).




**Fig. 5:** Reverse leakage current versus reverse voltage applied (typical values).




**Fig. 6:** Junction capacitance versus reverse voltage applied (typical values).




**Fig. 7:** Forward voltage drop versus forward current (maximum values).



**PACKAGE MECHANICAL DATA**  
TO-220AC




**PACKAGE MECHANICAL DATA**  
ISOWATT220AC




# STPS745D/F/G

## PACKAGE MECHANICAL DATA D<sup>2</sup>PAK (Plastic)



## FOOTPRINT DIMENSIONS (in millimeters)



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 1998 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - France - Germany - Italy - Japan - Korea - Malaysia - Malta - Mexico - Morocco - The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.

<http://www.st.com>