


SEMPACK® 1 Thyristor/ Diode Modules

SKKT 56 **SKKH 56**
SKKT 57 **SKKH 57**
SKKT 57B




V _{RSM}	V _{RRM}	(dv/dt) _{cr}	I _{TRMS} (maximum value for continuous operation)			
			95 A			
V	V	V/ μ s	I _{TAV} (sin. 180; T _{case} = 74 °C)			
			60 A			
500	400	500	–	–	SKKH 56/04 D	–
700	600	500	SKKT 56/06 D	SKKT 57/06 D	SKKH 56/06 D	SKKH 57/06 D
900	800	500	SKKT 56/08 D	SKKT 57/08 D ¹⁾	SKKH 56/08 D	SKKH 57/08 D
1300	1200	500	SKKT 56/12 D	–	SKKH 56/12 D	–
1300	1200	1000	SKKT 56/12 E	SKKT 57/12 E ¹⁾	–	SKKH 57/12 E
1500	1400	1000	SKKT 56/14 E	SKKT 57/14 E ¹⁾	SKKH 56/14 E	SKKH 57/14 E
1700	1600	1000	SKKT 56/16 E	SKKT 57/16 E ¹⁾	SKKH 56/16 E	SKKH 57/16 E
1900	1800	1000	SKKT 56/18 E	SKKT 57/18 E ¹⁾	SKKH 56/18 E	SKKH 57/18 E
2100	2000	1000	SKKT 56/20 E	SKKT 57/20 E ¹⁾	–	SKKH 57/20 E
2300	2200	1000	SKKT 56/22 E	SKKT 57/22 E ¹⁾	–	SKKH 57/22 E

Symbol	Conditions	SKKT 56 SKKH 56	SKKT 57 SKKT 57B SKKH 57
I _{TAV}	sin. 180; T _{case} = 74 °C	60 A	
I _D	T _{case} = 80 °C	55 A	
	B2/B6	57 A/68 A	100 A/130 A
I _{RMS}	T _{amb} = 45 °C; P 3/180	130 A/3 x 100 A	
	W1/W3	T _{amb} = 35 °C; P 3/180 F	
I _{TSM}	T _{vj} = 25 °C; 10 ms	1 500 A	
	T _{vj} = 125 °C; 10 ms	1 250 A	
i ² t	T _{vj} = 25 °C; 8,3 ... 10 ms	11 000 A ² s	
	T _{vj} = 125 °C; 8,3 ... 10 ms	8 000 A ² s	
t _{gd}	T _{vj} = 25 °C; I _G = 1 A; di _G /dt = 1 A/ μ s	1 μ s	
t _{gr}	V _D = 0,67 · V _{DRM}	2 μ s	
(di/dt) _{cr}	T _{vj} = 125 °C	150 A/ μ s	
t _q	T _{vj} = 125 °C	typ. 80 μ s	
I _H	T _{vj} = 25 °C;	typ. 150 mA; max. 250 mA	
I _L	T _{vj} = 25 °C; R _G = 33 Ω	typ. 300 mA; max. 600 mA	
V _T	T _{vj} = 25 °C; I _T = 200 A	max. 1,65 V	
V _{T(TO)}	T _{vj} = 125 °C	0,9 V	
r _T	T _{vj} = 125 °C	3,5 m Ω	
I _{DD} ; I _{RD}	T _{vj} = 125 °C; V _{DD} = V _{DRM} ; V _{RD} = V _{RRM}	max. 15 mA ³⁾	
V _{GT}	T _{vj} = 25 °C; d. c.	3 V	
I _{GT}	T _{vj} = 25 °C; d. c.	150 mA	
V _{GD}	T _{vj} = 125 °C; d. c.	0,25 V	
I _{GD}	T _{vj} = 125 °C; d. c.	6 mA	
R _{thjc}	cont. sin. 180 rec. 120 } per thyristor/per module	0,57 °C/W / 0,29 °C/W	
R _{thch}		0,60 °C/W / 0,30 °C/W	
T _{vj} , T _{stg}		0,64 °C/W / 0,32 °C/W	
V _{isol}	a. c. 50 Hz; r. m. s.; 1 s/1 min to heatsink } SI units / US units to terminals } M ₁ M ₂ a w approx.	3600 V – / 3000 V –	
M ₁		5 Nm/44 lb. in. \pm 15 % ²⁾	
M ₂		3 Nm/26 lb. in. \pm 15 %	
a		5 · 9,81 m/s ²	
w		120 g	
Case	→ page B 1 – 93	SKKT 56: A 5 SKKH 56: A 6	SKKT 57: A 46 SKKT 57B: A 48 SKKH 57: A 47




SKKT 56



SKKH 56



SKKT 57



SKKH 57

Features

- Heat transfer through aluminium oxide ceramic isolated metal baseplate
- Hard soldered joints for high reliability
- UL recognized, file no. E 63 532

Typical Applications

- DC motor control (e. g. for machine tools)
- AC motor soft starters
- Temperature control (e. g. for ovens, chemical processes)
- Professional light dimming (studios, theaters)

1) Also available in SKKT 57 B configuration (case A 48)

2) See the assembly instructions

3) /20 E, /22 E max. 30 mA




Fig. 1 Power dissipation per thyristor vs. on-state current and ambient temperature




Fig. 2 Power dissipation per module vs. rms current and case temperature




Fig. 3 Power dissipation of two modules vs. direct current and case temperature




Fig. 4 Power dissipation of three modules vs. direct and rms current and case temperature




Fig. 5 Recovered charge vs. current decrease




Fig. 6 Transient thermal impedance vs. time




Fig. 7 Thermal resistance vs. conduction angle




Fig. 8 On-state characteristics




Fig. 9 Surge overload current vs. time




Fig. 10 Gate trigger characteristics